



Eco StreetLine | Park LED Park luminaire

The Eco StreetLine family of top- and side-mounted post luminaires with an self-sufficient LED module, tailored to light classes S4 – S6 or ME6. Completely pre-fitted, with supply cables and module.

Sustainable concept in a timeless housing with Technology Warranty. Modules can be replaced with future versions to keep the luminaires state of the art.

The asymmetric light distribution is configurable as required. The power consumption can be reduced by 50 % with a phase-shedding.

The advantages of Eco StreetLine | Park:

- Modular LED system with integrated electronics
- Technology Warranty
- 5 year warranty on LED modules
- Average service life > 12 years (50,000 hours)
- At least 20 years availability of parts
- Modular light distribution
- Variable tilt setting between -15° and +15°
- Completely pre-fitted, with supply cables and module
- Dimming by 50 %
- Built-in overheating protection
- Maintenance-optimised design

LIGHT TECHNOLOGIES	
Colour temperature	5 K (cold white) 4 K (neutral white) optional 3 K (warm white)
Colour rendering index	CRI typ. 65 (5 K) CRI typ. 73 (4 K) CRI typ. 83 (3 K)
Luminous flux over lifetime	80% after 50,000 operating hours
Optics	LED-lenses made of PMMA, partially frosted cover lens made of PMMA (PC possible)

ELECTRICAL	
Lamp type	1 module with 8 LEDs
Electronic ballast	Electronically integrated into the module
Dimming	2-level operation via two supply cables (100% / 50% reduction)
Input Voltage	220 – 240 V / 50 Hz
Protection class	SK II
System power	Approx. 620 lm = 10 W (module 600) 800 lm = 13 W (module 800) 1,250 lm = 15 W (module 1,250) 1,700 lm = 21 W (module 1,700)
Power Factor	≥ 0.95
Overvoltage resistance	6 kV
Current capacity	2.5 kA
Cabling	Optionally installed connecting cables in various lengths or without cable
ADDITIONAL DATA	
Dimensions (L x W x H)	680 x 160 x 110 mm
Weight	6.5 kg
Materials	Housing trough and lamp base made of aluminium die casting, painted
Mast connection	60 mm or 76 mm Variable tilt setting between -15° and +15°
Wind area	FW = 0.08 m ²
Ambient temperature	-40°C to +55°C
Impact resistance	IK 04, optionally IK 06 and IK 08
Certification	IP67 IP69



Eco StreetLine | Twin

LED top- and side-mounted post luminaire

The Eco StreetLine family of top- and side-mounted post luminaires with two self-sufficient LED modules, tailored to lighting classes S2 – S5 or ME5 – ME6. Completely pre-fitted, with supply cables and modules.

Sustainable concept in a timeless housing with Technology Warranty. Modules can be replaced with future versions to keep the luminaires state of the art.

The asymmetric light distribution is configurable as required. The power consumption can be reduced by 50 % with a phase-shedding.

The advantages of Eco StreetLine | Twin:

- Modular LED system with integrated electronics
- Technology Warranty
- 5 year warranty on LED modules
- Average service life > 12 years (50,000 hours)
- At least 20 years availability of parts
- Modular light distribution
- Variable tilt setting between -15° and +15°
- Completely pre-fitted, with supply cables and modules
- Dimming by 50 %
- Built-in overheating protection
- Maintenance-optimised design

LIGHT TECHNOLOGIES

Colour temperature	5 K (cold white) 4 K (neutral white) optional 3 K (warm white)
Colour rendering index	CRI typ. 65 (5 K) CRI typ. 73 (4 K) CRI typ. 83 (3 K)
Luminous flux over lifetime	80% after 50,000 operating hours
Optics	LED-lenses made of PMMA, partially frosted cover lens made of PMMA (PC possible)

ELECTRICAL

Lamp type	2 modules with 8 LEDs
Electronic ballast	Electronically integrated into the module
Dimming	2-level operation via two supply cables (100% / 50% reduction)
Input Voltage	220 – 240 V / 50 Hz
Protection class	SK II
System power	Approx. 1,240 lm = 20 W (2 x module 600) 1,600 lm = 26 W (2 x module 800) 2,500 lm = 30 W (2 x module 1,250) 3,400 lm = 42 W (2 x module 1,700)
Power Factor	≥ 0.95
Overvoltage resistance	6 kV
Current capacity	2.5 kA
Cabling	Optionally installed connecting cables in various lengths or without cable

ADDITIONAL DATA

Dimensions (L x W x H)	680 x 220 x 110 mm
Weight	9.5 kg
Materials	Housing trough and lamp base made of aluminium die casting, painted
Mast connection	60 mm or 76 mm Variable tilt setting between -15° and +15°
Wind area	FW = 0.08 m ²
Ambient temperature	-40°C to +55°C
Impact resistance	IK 04, optionally IK 06 and IK 08

Certification





Eco StreetLine | Case

LED top- and side-mounted post luminaire

The Eco StreetLine family of top- and side-mounted post luminaires with four self-sufficient LED modules, tailored to light classes S1–S4 or ME3–ME6. Completely pre-fitted, with supply cables and modules.

Sustainable concept in a timeless housing with Technology Warranty. Modules can be replaced with future versions to keep the luminaires state of the art.

The asymmetric light distribution is configurable as required. The power consumption can be reduced by 50 % with a phase-shedding.

The advantages of the Eco StreetLine | Case:

- Modular LED system with integrated electronics
- Technology Warranty
- 5 year warranty on LED modules
- Average service life > 12 years (50,000 hours)
- At least 20 years availability of parts
- Modular light distribution
- Variable tilt setting between -15° and +15°
- Completely pre-fitted, with supply cables and modules
- Dimming by 50 %
- Built-in overheating protection
- Maintenance-optimised design

LIGHT TECHNOLOGIES

Colour temperature	5 K (cold white) 4 K (neutral white) optional 3 K (warm white)
Colour rendering index	CRI typ. 65 (5 K) CRI typ. 73 (4 K) CRI typ. 83 (3 K)
Luminous flux over lifetime	80% after 50,000 operating hours
Optics	LED-lenses made of PMMA, partially frosted cover lens made of PMMA (PC possible)

ELECTRICAL

Lamp type	4 modules with 8 LEDs
Electronic ballast	Electronically integrated into the module
Dimming	2-level operation via two supply cables (100% / 50% reduction)
Input Voltage	220–240 V / 50 Hz
Protection class	SK II
System power	Approx. 2,480 lm = 40 W (4 x module 600) 3,200 lm = 52 W (4 x module 800) 5,000 lm = 60 W (4 x module 1,250) 6,800 lm = 84 W (4 x module 1,700)
Power Factor	≥ 0.95
Overvoltage resistance	6 kV
Current capacity	2.5 kA
Cabling	Optionally installed connecting cables in various lengths or without cable

ADDITIONAL DATA

Dimensions (L x W x H)	680 x 440 x 110 mm
Weight	14.5 kg
Materials	Housing trough and lamp base made of aluminium die casting, painted
Mast connection	60 mm or 76 mm Variable tilt setting between -15° and +15°
Wind area	FW = 0.08 m ²
Ambient temperature	-40°C to +55°C
Impact resistance	IK 04, optionally IK 06 and IK 08
Certification	IP67 IP69



MODULE 1700 lm
21 WATT INNOVATION
 CONTINUED

Eco StreetLine | Square LED Post-Top Luminaire

LED Post-Top Luminaire of the Eco StreetLine family with four self-sufficient LED modules, tailored to light classes S1 – S4 or ME3 – ME6. Completely pre-fitted, with supply cables and modules.

Sustainable concept in a timeless housing with Technology Warranty. Modules can be replaced with future versions to keep the luminaires state of the art.

The asymmetric light distribution is configurable as required. The power consumption can be reduced by 50 % with a phase-shedding.

The advantages of Eco StreetLine | Square:

- Modular LED system with integrated electronics
- Technology Warranty
- 5 year warranty on LED modules
- Average service life > 12 years (50,000 hours)
- At least 20 years availability of parts
- Modular light distribution
- Completely pre-fitted, with supply cables and modules
- Dimming by 50 %
- Built-in overheating protection
- Maintenance-optimised design

LIGHT TECHNOLOGIES

Colour temperature	5 K (cold white) 4 K (neutral white) optional 3 K (warm white)
Colour rendering index	CRI typ. 65 (5 K) CRI typ. 73 (4 K) CRI typ. 83 (3 K)
Luminous flux over lifetime	80% after 50,000 operating hours
Optics	LED-lenses made of PMMA, partially frosted cover lens made of PMMA (PC possible)

ELECTRICAL

Lamp type	4 modules with 8 LEDs
Electronic ballast	Electronically integrated into the module
Dimming	2-level operation via two supply cables (100% / 50% reduction)
Input Voltage	220 – 240 V / 50 Hz
Protection class	SK II
System power	Approx. 2,480 lm = 40 W (4 x module 600) 3,200 lm = 52 W (4 x module 800) 5,000 lm = 60 W (4 x module 1,250) 6,800 lm = 84 W (4 x module 1,700)
Power Factor	≥ 0.95
Overvoltage resistance	6 kV
Current capacity	2.5 kA
Cabling	Optionally installed connecting cables in various lengths or without cable

ADDITIONAL DATA

Dimensions (L x W x H)	700 x 700 x 500 mm
Weight	15.5 kg
Materials	Housing trough and lamp base made of aluminium die casting, housing stays of aluminium extruded sections, painted
Mast connection	76 mm
Wind area	FW = 0.15 m ²
Ambient temperature	-40°C to +55°C
Impact resistance	IK 04, optionally IK 06 and IK 08
Certification	IP67 IP69