



Technology
with Vision



MODUL 1700 lm
21 WATT INNOVATION
CONTINUED



Double-module functional light
with connection box or
5.00 m / 10.00 m connection cable

Eco IndustryLine Double-module functional light

Ceiling surfaced-mounted luminaire made of robust aluminium housing (painted RAL 9006) based on a modular LED solution with fully integrated electronics for various applications. LED-Module with different optics for various light distribution requirements available. The power consumption can be reduced by 50 % with a phase-shedding. Sustainable concept with technology guarantee. Modules can be replaced with future module versions to ensure state of the art technology.

ELECTRICAL	
Lamp type	2 LED-modules with 8 LEDs each
Electronic ballast	integrated into the module
Triggerung	2-level operation via two supply cables (100 % / 50 % reduction)
Input voltage	220–240 V / 50 Hz
Protection class	SK II
System power	2 x 13 W = 26 W (module 800) 2 x 15 W = 30 W (module 1,250) 2 x 21 W = 42 W (module 1,700)
Efficiency factor	≥ 0.95
Overload resistance	6 kV
Peak withstand current	2.5 kA
Connection	Connection box or connection cables
LICHTTECHNIK	
System luminous flux	1,600 lm (2 x module 800) 2,500 lm (2 x module 1,250) 3,400 lm (2 x module 1,700)
Luminous flux over lifetime	80 % after 50,000 operating hours
Colour temperature	optionally 5,000 K (cold white) or 4,000 K (neutral white)
Colour rendering index	CRI typ. 73 (4,000 K) CRI typ. 65 (5,000 K)
Optics	LED-lenses made of PMMA, partially frosted cover lens made of PMMA (PC possible)
Operating temperature	-40°C to +55°C

ADDITIONAL DATA	
Dimensions (L x W x H)	980 x 103 x 105 mm
Weight	5.2 kg (incl. LED-module and connection box) 5.5 kg (incl. LED-module and 5.00 m cable) 5.7 kg (incl. LED-module and 10.00 m cable)
Materials	Housing made of aluminium die casting, painted (RAL 9006), connection box and endcaps made of PC
IP Certification (Luminaire)	IP 65
Mounting	Direct screw coupling for ceiling surfaced mounting
Connection room	Supply line 2 x (5-pin 1 mm ² to 2,5 mm ² , rigid cable possible), cable gland M16 for Ø 6 mm – 12 mm
PART NUMBERS*	
8NF 011 600-007/-008	Housing with connection box
8NF 011 600-017/-018	Housing with 5.00 m connection cable
8NF 011 600-027/-028	Housing with 10.00 m connection cable

* LED-module is not included.
All performance parameters refer to an ambient temperature of 25°C.

Issue 01/2013